

Global Stability Analysis of an End-to-End Congestion Control Scheme for General Topology Networks with Delay ¹

Tansu Alpcan and Tamer Başar

Coordinated Science Laboratory, University of Illinois

1308 West Main Street, Urbana, IL 61801 USA

(alpcan, tbasar)@control.csl.uiuc.edu

Abstract— We analyze the stability properties of an end-to-end congestion control scheme under fixed heterogeneous delays, and for general network topologies. The scheme analyzed is based on the congestion control game of [1], with the starting point being the unique Nash equilibrium of that game. We prove global stability of this solution (and hence of the congestion control algorithm) under a mild symmetricity condition. We further demonstrate the stability of the algorithm numerically for various delays, user numbers, and topologies.

I. INTRODUCTION

In communication networks, delays between users and resources of the network are most of the time not negligible. In the context of the Internet, these delays vary from order of tens to hundreds of milliseconds, and affect the stability of end-to-end congestion control algorithms. The communication delays in the network are in general heterogeneous in the sense that forward delays between the users and the resources are different from the feedback delays. It is possible to consider end-to-end congestion control schemes in this setting as feedback systems with delay where users vary their flow rates in accordance with the delayed feedback they receive from the system resources. Depending on the specific network, this feedback signal may be in the form of packet losses as in Transfer Control Protocol (TCP), marked packets or variations in round trip time (RTT) the packets experience.

Several congestion control and pricing algorithms have been introduced in [2]–[5], whose stability properties have recently been investigated in the presence of non-negligible delays [6]–[8]. Johari and Tan [8] have analyzed the local stability of a delayed system where the end user implements the ‘primal algorithm’ ([2], [3]) which is a TCP-like rate control algorithm. They have considered a single link accessed by a single user, as well as its multiple user extension under the assumption of symmetric delays. In both cases, they have provided sufficient conditions for local stability of the underlying system of equations. Massoulié [7] has extended these results to general network topologies and heterogeneous delays. In another study, Vinnicombe [6] has also provided sufficient conditions for local stability of a user source law which is a generalization of the same algorithm.

Within the distributed congestion control framework of [2], [3], Kunniyur and Srikant [9] have examined the question of how to provide the congestion feedback from the network to

the user. They have proposed an explicit congestion notification (ECN) marking scheme combined with dynamic adaptive virtual queues, and have shown using a time-scale decomposition that the system is semi-globally stable in the no-delay case. Deb and Srikant [10], on the other hand, have focused on the case of single user and a single resource, and have investigated sufficient conditions for global stability of various congestion control schemes. Liu, Başar, and Srikant [11] have extended the framework of [2], [3] by introducing a primal-dual algorithm, which has dynamic adaptations at both ends (users and links), and have given a condition for its local stability using the generalized Nyquist criterion. Wen and Arcak [12] have used the passivity framework to unify some of the stability results on primal and dual algorithms without delay, have introduced and analyzed a larger class of such algorithms for stability, and have shown robustness to variations due to delay. In another recent study, Alpcan and Başar [13] have proposed a similar scheme based on game theory, where queuing delays in the network are used as congestion feedback. They have also provided sufficient conditions for global stability at a bottleneck link under non-negligible communication delays.

In this paper, we analyze in the presence of heterogeneous delays the global stability of the congestion control and pricing scheme introduced earlier in [1], which is based on noncooperative game theory. We provide sufficient conditions for the global stability under heterogeneous delays on a general topology network. Specifically, we make a mild symmetricity assumption on the variation of aggregate flows at links with respect to individual delays. We note that the condition obtained for the global stability shares a similar structure with the local stability results obtained in the earlier studies [6]–[8].

The rest of the paper is organized as follows: In Section II we introduce the network model as well as the game theory based congestion control framework, and state the existence and uniqueness of a Nash equilibrium (NE) solution. Global stability of this NE is established under a gradient algorithm in Section III for the ideal -no delay- case. Section IV contains the stability analysis and sufficient conditions for global stability of the same algorithm in the presence of heterogeneous delays. In Section V we illustrate the theoretical results obtained numerically. The paper concludes with the remarks of Section VI.

¹Research supported in part by the NSF Grants CCR 00-85917 and ECS 02-25481.

II. A CONGESTION CONTROL GAME

The network model and the congestion control game in this section have been introduced in our earlier study [1]. They are presented here in a concise form for completeness. We consider a general network model based on fluid approximations, similar to the one in [13]. The topology of the network is characterized by a set of nodes $\mathcal{N} = \{1, \dots, N\}$ and a set of links connecting the nodes, $\mathcal{L} = \{1, \dots, L\}$, with each link $l \in \mathcal{L}$ having a fixed positive capacity $c_l > 0$, and an associated buffer size $b_l \geq 0$. There are M users sharing the network, with the set of users being $\mathcal{M} = \{1, \dots, M\}$. Each user is associated with a unique *connection*, or path R between a source and a destination node. The i^{th} user sends its nonnegative flow, $x_i \geq 0$, over its path R_i . A routing matrix, $\mathbf{A} := [(a_{l,i})]$ of ones and zeros, is defined as in [2], which describes the relation between the set of routes $\mathcal{R} = \{1, \dots, M\}$ associated with the users (connections) and links $l \in \mathcal{L}$. We assume without any loss of generality that \mathbf{A} has no rows or columns that are identically zero.

Using the routing matrix \mathbf{A} , the capacity constraints of the links are given by $\mathbf{A}\mathbf{x} \leq \mathbf{c}$, where \mathbf{x} is the $(M \times 1)$ flow rate vector of users and \mathbf{c} is the $(L \times 1)$ link capacity vector. The flow rate vector, \mathbf{x} , is said to be feasible if it is nonnegative and satisfies this constraint. Let \mathbf{x}_{-i} be the flow rate vector of all users except the i^{th} one. For a given fixed, feasible \mathbf{x}_{-i} , there exists a strict finite upper-bound $m_i(\mathbf{x}_{-i})$ on flow rate, x_i , of the i^{th} user based on the capacity constraints of the links:

$$m_i(\mathbf{x}_{-i}) = \min_{l \in R_i} (c_l - \sum_{j \neq i} A_{l,j} x_j) \geq 0.$$

For the given general topology network model, we propose a network game with M users. It is assumed that the routing problem has already been solved and individual routes, $R \in \mathcal{R}$, do not change during the connection. Our analysis is based on noncooperative game theory. Here, the users are noncooperative in the sense that they have no means of communicating with each other about their preferences, and each user tries to optimize his usage of the network independently. A specific cost function, J , is assigned to each user, which will be indexed by i for user i . This cost function not only models the user preferences but it also includes a feedback term capturing the current network state. The i^{th} user minimizes his cost, J_i , by adjusting his flow rate $0 \leq x_i \leq m_i(\mathbf{x}_{-i})$ given the fixed, feasible flow rates of all other users on its path, $\{x_j : j \in (R_j \cap R_i)\}$.

The cost function of the i^{th} user, J_i , is the difference between a user-specific pricing function, P_i , and a utility function, U_i . The pricing function P_i depends on the current state of the network, and can be interpreted as the price a user pays for using the network resources. The utility function of the i^{th} user is defined to be increasing and concave in accordance with elastic traffic as well as with the economic principle, law of diminishing returns. We focus on the bandwidth as the main resource in the system. Therefore, the utility of the i^{th} user

depends only on its own flow rate. Thus, the cost function is defined as

$$J_i(\mathbf{x}; \mathbf{c}, \mathbf{A}) = P_i(\mathbf{x}; \mathbf{c}, \mathbf{A}) - U_i(x_i).$$

We note that P_i does not necessarily depend on the flow rates of all other users; it can be structured to depend only on the flow rates of the users sharing the same links on the path of user i .

In the given context of the network game, the Nash equilibrium is defined as a set of flow rates, \mathbf{x}^* (and corresponding costs J^*), with the property that no user can benefit by modifying its flow while the other players keep theirs fixed. Furthermore, if the Nash equilibrium, \mathbf{x}^* , meets the capacity constraints as well as the positivity constraint with strict inequality, then it is an *inner* solution. Mathematically speaking, \mathbf{x}^* is in Nash Equilibrium, when x_i^* of any i^{th} user is the solution to the following optimization problem given that all users on its path have equilibrium flow rates, \mathbf{x}_{-i}^* :

$$\min_{0 \leq x_i \leq m_i(\mathbf{x}_{-i}^*)} J_i(x_i, \mathbf{x}_{-i}^*, \mathbf{c}, \mathbf{A}), \quad (1)$$

where \mathbf{x}_{-i} denotes the collection $\{x_j : j \in R_j \cap R_i\}_{j=1, \dots, M}$. To proceed further, we make the following two assumptions.

A1. $P_i(\mathbf{x})$ is jointly continuous in all its arguments and twice continuously differentiable, non-decreasing and convex in x_i , i.e.

$$\partial P_i(\mathbf{x}) / \partial x_i \geq 0, \quad \partial^2 P_i(\mathbf{x}) / \partial x_i^2 \geq 0. \quad (2)$$

A2. $U(x_i)$ is jointly continuous in all its arguments and twice continuously differentiable, non-decreasing and strictly concave in x_i , i.e.

$$\partial U_i(x_i) / \partial x_i \geq 0, \quad \partial^2 U_i(x_i) / \partial x_i^2 < 0, \quad \forall x_i$$

Moreover, the optimal solution is an *inner* one, $0 < \sum_j A_{l,j} x_j^* < c_l, \forall l$, under the additional assumption:

A3. The i^{th} user's cost function has the following properties at $x_i = 0$ ($x_i = m_i(\mathbf{x}_{-i})$): $\partial J_i(\mathbf{x} : x_i = 0) / \partial x_i < 0 \forall \mathbf{x}$ ($\partial J_i(\mathbf{x} : x_i = m_i(\mathbf{x}_{-i})) / \partial x_i > 0 \forall \mathbf{x}$), respectively.

Theorem II.1 below establishes that the congestion control game admits a unique NE under the following further assumption:

A4. The price function $P_i(\mathbf{x})$ of the i^{th} user is defined as the sum of link price functions on its path,

$$P_i = \sum_{l \in R_i} P_l \left(\sum_{j: l \in R_j} x_j \right),$$

where P_l is defined as a function of the aggregate flow on link l , and satisfies (2) with i replaced by l .

Theorem II.1. *Under A1-A4, the network game admits a unique inner Nash equilibrium.*

The proof of this theorem can be found in [1].

III. GLOBAL STABILITY IN THE DELAY-FREE CASE

We consider a simple dynamic model of the network game where each user changes his flow rate in proportion with the gradient of his cost function with respect to his flow rate. Note that this corresponds to the well-known steepest descent algorithm in nonlinear programming [14]. Hence, the user update algorithm is:

$$\begin{aligned}\dot{x}_i(t) &= \frac{dx_i(t)}{dt} = -\frac{\partial J_i(\mathbf{x}(t))}{\partial x_i} \\ &= \frac{dU_i(x_i)}{dx_i} - \sum_{l \in R_i} f_l \left(\sum_{j \in \mathcal{M}_l} x_j \right) := \Theta_i(\mathbf{x}),\end{aligned}\quad (3)$$

for all $i = 1, \dots, M$, where $\mathcal{M}_l(M_l)$ is the set (number) of users whose flows pass through the link, $l \in R_i$; t is the time variable, which we drop in the second line for a more compact notation; and f_l is defined as $f_l(\cdot) := \partial P_l(\cdot)/\partial x_i$.

By assumption A4, the partial derivative of f_l with respect to x_i , $\partial f_l(\cdot)/\partial x_i$, is non-negative. Furthermore, since $P_l(\mathbf{x})$ is convex and jointly continuous in x_i for all i whose flows pass through the link l , on the compact set of feasible flow rate vectors, $X := \{\mathbf{x} \in \mathbb{R}^M : \mathbf{A}\mathbf{x} \leq \mathbf{c}, \mathbf{x} \geq 0\}$, the derivative $\partial f_l(\cdot)/\partial x_i$ can be bounded above by a constant $\alpha_l > 0$. Hence,

$$0 \leq \frac{\partial f_l(\bar{x}_i)}{\partial x_i} \leq \alpha_l, \quad (4)$$

where $\bar{x}_i = \sum_{i \in \mathcal{M}_l} x_i$.

Next, we establish the result that the system defined by (3) is asymptotically stable on the set X , which is invariant by assumption A3 under the gradient update algorithm (3). In order to see the invariance of X , we investigate each boundary of X separately. When $x_i = 0$ for some $i \in \mathcal{M}$, we have $\dot{x}_i > 0$ from (3) under assumption A3 due to the gradient descent algorithm of user i . Hence, the system trajectory moves toward inside of X . Likewise, in the case of $\bar{x}_l = c_l$ for some $l \in \mathcal{L}$, it follows from (3) and assumption A3 that $\dot{x}_i < 0 \forall i \in \mathcal{M}_l$, and hence, the trajectory remains inside the set X .

The equilibrium state of the system (3) in X is of course the unique NE, \mathbf{x}^* , referred to in Theorem II.1. Let us define a candidate Lyapunov function $V : \mathbb{R}^M \rightarrow \mathbb{R}^+$ as

$$V(\mathbf{x}) := \frac{1}{2} \sum_{i=1}^M \Theta_i^2(\mathbf{x}),$$

which is in fact restricted to the domain X . Further let $\Theta := [\Theta_1, \dots, \Theta_M]$. Taking the derivative of V with respect to t on the trajectories generated by (3), we obtain

$$\dot{V}(\mathbf{x}) = \sum_{i=1}^M \frac{d^2 U_i(x_i)}{dx_i^2} \Theta_i^2(\mathbf{x}) - \Theta^T(\mathbf{x}) A^T K A \Theta(\mathbf{x}),$$

where A is the routing matrix, and K is a diagonal matrix defined as $K := \text{diag} \left[\frac{\partial f_1(\bar{x})}{\partial \bar{x}}, \frac{\partial f_2(\bar{x})}{\partial \bar{x}}, \dots, \frac{\partial f_M(\bar{x})}{\partial \bar{x}} \right]$.

Since $A^T K A$ is non-negative definite and $d^2 U_i/dx_i^2$ is uniformly negative definite, $V(\mathbf{x})$ is strictly decreasing, $\dot{V}(\mathbf{x}) < 0$, on the trajectory of (3). Thus, the system is asymptotically

stable on the invariant set X by Lyapunov's stability theorem (see Theorem 3.1 in [15]).

Theorem III.1. *Assume A1-A4 hold. Then, the unique Nash equilibrium of the network game is globally stable on the compact set of feasible flow rate vectors, $X := \{\mathbf{x} \in \mathbb{R}^M : \mathbf{A}\mathbf{x} \leq \mathbf{c}, \mathbf{x} \geq 0\}$ under the gradient algorithm given by*

$$\dot{x}_i = -\frac{\partial J_i(\mathbf{x})}{\partial x_i}, \quad i = 1, \dots, M.$$

IV. GLOBAL STABILITY UNDER BOUNDED AND HETEROGENEOUS COMMUNICATION DELAYS

We now investigate global stability of the gradient algorithm (3) under bounded and heterogeneous communication delays. The pricing function of the i^{th} user is defined in accordance with assumption A4 as

$$P_i = \sum_{l \in R_i} P_l \left(\sum_{j \in \mathcal{M}_l} x_j \right),$$

where R_i is the path (route) of user i , and P_l is the pricing function at link $l \in \mathcal{L}$. The update algorithm with communication delays is then given by

$$\dot{x}_i(t) = \frac{dU_i(x_i(t))}{dx_i} - \sum_{l \in R_i} f_l \left(\sum_{j \in \mathcal{M}_l} x_j(t - r_{li} - r_{lj}) \right) \quad (5)$$

where r_{li} and r_{lj} are fixed communication delays between the l^{th} link and the i^{th} and j^{th} users respectively.¹ To simplify the notation we define

$$\bar{x}_i^i(t - r) := \sum_{j \in \mathcal{M}_l} x_j(t - r_{li} - r_{lj}).$$

In addition, let q be an upper-bound on the maximum round-trip time (RTT) in the system:

$$q := 2 \max_i \sum_{l \in R_i} r_{li} - r_{(l-1)i},$$

where $r_{0i} = 0 \forall i$. Finally, define $\mathbf{x}_t := \{\mathbf{x}(t + s), -q \leq s \leq 0\}$, and by a slight abuse of notation let $\Theta_i(\mathbf{x}_t)$ denote the right hand side of (5).

We next make use of the stability theory for autonomous systems of [16], and generalize the scalar analysis of [17] and also of Chapter 5.4 of [16] to the multidimensional (multi-user) case. Let $\phi_i \in C([-r_i, 0], \mathbb{R})$ be a feasible flow rate function (initial condition) for the i^{th} user's dynamics (5) at time $t = 0$, where C is the set of continuous functions. In addition, let $\mathbf{x}(\phi)(t)$ be the solution of (5) through ϕ for $t \geq 0$, and $\dot{\mathbf{x}}(\phi)(t)$ be its derivative. In order to simplify the notation, we will use $\mathbf{x}(\phi)$ and \mathbf{x} as well as $\Theta(\phi)$ and Θ and their respective derivatives interchangeably for the remainder of the paper.

A continuously differentiable and positive function $V : C^M \rightarrow \mathbb{R}^+$ is defined as

$$V(\mathbf{x}_t(\phi)) := \frac{1}{2} \sum_{i=1}^M \Theta_i^2(\mathbf{x}_t(\phi)) = \frac{1}{2} \Theta^T(\mathbf{x}_t(\phi)) \Theta(\mathbf{x}_t(\phi)).$$

¹Here we implicitly make the assumption that queuing delays are negligible compared to the fixed propagation delays in the system.

We introduce the candidate Lyapunov function $\bar{V} : \mathbb{R}^+ \times C^M \rightarrow \mathbb{R}^+$,

$$\bar{V}(t; \phi) := \sup_{t-2q \leq s \leq t} V(\mathbf{x}_s(\phi)).^2$$

In order for $\bar{V}(t; \phi)$ to be non-increasing, $\dot{\bar{V}}(t; \phi) \leq 0$, the set

$$\Phi = \{\phi \in C : \bar{V}(t; \phi) = V(\mathbf{x}_t(\phi)); \dot{V}(\mathbf{x}_t(\phi)) > 0 \forall t \geq 0\} \quad (6)$$

has to be empty. We now show that this is indeed the case.

Assume otherwise. Then, for any given t , there exists an $\epsilon > 0$ such that

$$\bar{V}(t; \phi) = V(\mathbf{x}_t(\phi)) = \sum_{i=1}^M \Theta_i^2(\mathbf{x}_t(\phi)) = \epsilon \quad (7)$$

and

$$V(\mathbf{x}_s(\phi)) = \sum_{i=1}^M \Theta_i^2(\mathbf{x}_s) \leq \epsilon, \quad s \in [t-2q, t].$$

Thus, the following bound on Θ_i , and thus on \dot{x}_i , follows immediately:

$$|\Theta_i(\mathbf{x}_s)| = |\dot{x}_i(s)| \leq \sqrt{\epsilon}, \quad s \in [t-2q, t]. \quad (8)$$

Taking the derivative of $\dot{x}_i(t)$ with respect to t , we obtain

$$\begin{aligned} \ddot{x}_i(t) &= \frac{\partial \dot{x}_i(t)}{\partial t} = \dot{\Theta}_i(\mathbf{x}_t) = \frac{d^2 U_i(x_i)}{dx_i^2} \dot{x}_i(t) \\ &\quad - \sum_{l \in R_i} \frac{\partial f_l(\bar{x}_l^i(t-r))}{\partial \bar{x}_l^i} \sum_{j \in \mathcal{M}_l} \dot{x}_j(t-r_i-r_j). \end{aligned} \quad (9)$$

Let $\delta_i := -\min_{x_i \in X} \frac{d^2 U_i(x_i)}{dx_i^2} > 0$. Using (8) and (9), it is possible to bound $\dot{\Theta}_i(\mathbf{x}_s)$ and $\ddot{x}_i(s)$ on $s \in [t-q, t]$ with

$$\begin{aligned} |\dot{\Theta}_i(\mathbf{x}_s)| = |\ddot{x}_i(s)| &\leq \delta_i |\dot{x}_i(s)| \\ &\quad + \sum_{l \in R_i} \frac{\partial f_l(\bar{x}_l^i(s-r))}{\partial \bar{x}_l^i} |\bar{x}_l^i(s-r)| \\ &\leq (\delta_i + \sum_{l \in R_i} M_l \alpha_l) \sqrt{\epsilon}. \end{aligned} \quad (10)$$

To simplify the notation, define

$$y_i := \delta_i + \sum_{l \in R_i} M_l \alpha_l.$$

Hence, we have the following bound on $\Theta_i(\mathbf{x}_s)$, $s \in [t-q, t]$:

$$\Theta_i(\mathbf{x}_t) - q y_i \sqrt{\epsilon} \leq \Theta_i(\mathbf{x}_s) \leq \Theta_i(\mathbf{x}_t) + q y_i \sqrt{\epsilon}. \quad (11)$$

We next show that $V(\mathbf{x}_t(\phi))$ is non-increasing, and obtain a contradiction to the initial hypothesis that the set Φ is not empty. Assume that $\partial f_l(\bar{x}_l^i(t-r))/\partial \bar{x}_l^i = \partial f_l(\bar{x}_l^i(t-r))/\partial \bar{x}_l^j$, $\forall i, j \in \mathcal{M}_l$, $\forall t$ for each link l . This assumption holds for example when f_l is linear in its argument. Let B be defined in such a way that $B^T B := A^T K A$, where the positive diagonal

matrix K is defined in Section III. Also define the positive diagonal matrix

$$D(\mathbf{x}) := \text{diag}[|D_1(x_1)|, |D_2(x_2)|, \dots, |D_M(x_M)|],$$

where $D_i(\mathbf{x}) := d^2 U_i(x_i)/dx_i^2$. Then, using (11), we obtain

$$\begin{aligned} \dot{V}(\mathbf{x}_t) &= - \sum_{i=1}^M D_i(x_i) \Theta_i^2(\mathbf{x}_t) - \sum_{i=1}^M \Theta_i(\mathbf{x}_t) \\ &\quad \cdot \sum_{l \in R_i} \frac{\partial f_l(\bar{x}_l^i(t-r))}{\partial \bar{x}_l^i} \sum_{j \in \mathcal{M}_l} \Theta_j(\mathbf{x}_{t-r_{li}-r_{lj}}) \\ &\leq -\Theta^T D \Theta - \Theta^T B^T B \Theta + q \sqrt{\epsilon} |\Theta^T B^T B \mathbf{y}|, \end{aligned} \quad (12)$$

where everything is evaluated at t . Now, for any fixed trajectory generated by (5), and for a frozen time t , a sufficient condition for $\dot{V}(\mathbf{x}_t) \leq 0$ is

$$q \sqrt{\epsilon} \leq \frac{\|B \Theta\|^2 + \|\sqrt{D} \Theta\|^2}{\|B \Theta\| \|\mathbf{B} \mathbf{y}\|},$$

where $\|\cdot\|$ is the Euclidean norm.

Let $k := \frac{\|B \Theta\|}{\|\mathbf{B} \mathbf{y}\|} > 0$. Rewriting the sufficient condition we obtain

$$q \sqrt{\epsilon} \leq k + \frac{1}{k} \mu,$$

where $\mu := \frac{\|\sqrt{D} \Theta\|^2}{\|\mathbf{B} \mathbf{y}\|^2} > 0$. The following worst-case bound on q can be derived by a simple minimization:

$$q \sqrt{\epsilon} \leq 2\sqrt{\mu}. \quad (13)$$

We next find a lower bound on μ . From (7), it follows that $\|\sqrt{D} \Theta(\mathbf{x}_t)\|^2 \geq \bar{d} \epsilon$, where $\bar{d} := \min_i \min_{x_i \in X} \left| \frac{d^2 U_i(x_i)}{dx_i^2} \right|$, and \sqrt{D} is the unique positive definite matrix whose square is D . Furthermore,

$$\|\mathbf{B} \mathbf{y}\|^2 \leq \sum_{i=1}^M y_i \sum_{l \in R_i} \alpha_l \sum_{j \in \mathcal{M}_l} y_j.$$

Define also the following upper-bound on y_i :

$$b := \max_i \left(\delta_i + \sum_{l \in R_i} M_l \alpha_l \right)$$

Since $\delta_i > 0$, one obtains $\|\mathbf{B} \mathbf{y}\|^2 \leq M b^3$, and hence

$$\mu \geq \frac{\bar{d} \epsilon}{M b^3}.$$

Thus, from (13) a sufficient condition for $V(\mathbf{x}_t)$ to be non-increasing is

$$q \leq \frac{2\sqrt{\bar{d}}}{\sqrt{M} b^{3/2}}, \quad (14)$$

which now holds for all $t \geq 0$.

Finally, we make use of Definition 3.1 and Theorem 3.1 of [16] to establish global asymptotic stability of the system (5). Let $S := \{\phi \in C : \bar{V}(t; \phi) = \dot{V}(\mathbf{x}_t(\phi)) = 0\}$. From (5) and (12) it follows that

$$\begin{aligned} S' &= \{\phi \in C : \phi(\tau) = \mathbf{x}^*, -q \leq \tau \leq 0\} \subset S, \text{ as} \\ \Theta(\mathbf{x}_\tau) = \dot{\mathbf{x}}(\tau) = 0 &\Leftrightarrow \mathbf{x}_\tau = \mathbf{x}^* \Rightarrow \dot{V}(\mathbf{x}_\tau) = 0. \end{aligned}$$

²Without any loss of generality, we define $V(\mathbf{x}_s) = 0$, $s \in [-2q, -q]$.

Hence, S' is the largest invariant set in S , and for any trajectory of the system that belongs identically to S , we have $\mathbf{x}_\tau = \mathbf{x}^*$. In other words, the only solution that can stay identically in S is the unique equilibrium of the system. This then leads to the following theorem:

Theorem IV.1. *Assume that*

$$\partial f_i(\bar{x}_i^j(s-r))/\partial \bar{x}_i^j = \partial f_l(\bar{x}_l^j(s-r))/\partial \bar{x}_l^j, \forall i, j \in \mathcal{M}_l \forall t.$$

Then, the unique Nash equilibrium of the network game is globally asymptotically stable on the compact set of feasible flow rate vectors, $X := \{\mathbf{x} \in \mathbb{R}^M : \mathbf{A}\mathbf{x} \leq \mathbf{c}, \mathbf{x} \geq 0\}$ under the gradient algorithm

$$\dot{x}_i(t) = \frac{dU_i(x_i(t))}{dx_i} - \sum_{l \in R_i} f_l \left(\sum_{j \in \mathcal{M}_l} x_j(t - r_{li} - r_{lj}) \right),$$

in the presence of fixed heterogeneous delays, $r_{li} \geq 0$, for all users $i = 1, \dots, M$, and links $l \in \mathcal{L}$, if the following condition is satisfied

$$q \leq \frac{2\sqrt{\bar{d}}}{\sqrt{M}b^{3/2}},$$

where

$$b := \max_i \left(-\min_{x_i \in X} \frac{d^2 U_i(x_i)}{dx_i^2} + \sum_{l \in R_i} M_l \alpha_l \right),$$

and

$$\bar{d} := \min_i \min_{x_i \in X} \left| \frac{d^2 U_i(x_i)}{dx_i^2} \right|.$$

Remark IV.2. If the user reaction function is scaled by a user-independent gain constant, λ , then the i^{th} user's response is given by

$$\dot{x}_i = -\lambda \frac{\partial J_i(\mathbf{x}(t))}{\partial x_i},$$

and the sufficient condition for global stability turns out to be

$$q \leq \frac{2\sqrt{\bar{d}}}{\sqrt{M}\lambda^{3/2}b^{3/2}}.$$

Notice that, for any $\lambda < 1$, the upper-bound on maximum RTT, q , is relaxed proportionally with $\lambda^{3/2}$.

V. NUMERICAL EVALUATION

The results presented in Section IV are evaluated numerically using MATLAB. The delay differential equations are solved using the delay differential solver, *dde23* [18]. The utility function for the i^{th} user is chosen as

$$U_i = u_i \log(x_i + 1),$$

where u_i is a user-specific positive preference parameter. The pricing function at the link l is defined as

$$P_l = \frac{\alpha}{2} \left(\sum_{j:l \in R_j} x_j \right)^2,$$

where α is the pricing constant. We choose here the cost function, cost parameters, and link capacities in accordance

with assumptions *A1-A4*.³ In the case of a single link shared by M users, the user update algorithm follows directly from (5), and is given by

$$\dot{x}_i(t) = \frac{u_i}{x_i(t) + 1} - \alpha \sum_{j:l \in R_j} x_j(t - r_j - r_i), \quad \forall i = 1, \dots, M.$$




Fig. 1. Flow rate versus time of a single-user on a single-link with utility and pricing functions $U = \log(x + 1)$, $P = \frac{1}{2}x^2(t - 2r)$, and communication delays (from top to bottom) $r = 0.5, 1, 2$.




Fig. 2. Flow rates of two and four users versus time under the delay $r_i = 0.5, \forall i$ shown in (a) and (b), respectively.

We first investigate single-user on a single-link case for illustrative purposes. The parameters in user's cost function are chosen as $u = 1$ and $\alpha = 1$. We simulate the system under communication delays of $r = 0.5, 1$, and 2 as observed in Figure 1. From Theorem IV.1, the condition for stability is calculated as $r < 0.42$. Since this condition is only sufficient the system could remain stable for $r > 0.42$, which is indeed what happens. However, the rate of convergence decreases significantly for increasing r , and for delays $r > 2$ the system becomes unstable. The effect of the number of users on system

³We note, however, that in a network implementation cost parameters α and u can be adjusted "online" through an adaptive algorithm, which takes capacity constraints on the network into account, in order to satisfy *A3* and make the NE an inner solution.




Fig. 3. Flow rates of 10 users versus time with origin as the starting point (a), and random initial conditions (b).

stability is demonstrated in the next simulation. The delay in the system is symmetric and chosen as $r_i = 0.5$, $\forall i$. Figure 2 shows that increasing the number of users has a similar effect as increasing the delay as captured in Theorem IV.1.

In the next set of simulations, the number of users sharing a single link is $M = 10$. The user utility parameters, u_i and delay r_i are randomly chosen with uniform distribution in the ranges $u_i \in [10, 20]$ and $r_i \in [0.1, 0.5]$, respectively. Figure 3a shows flow rates of individual users for the initial condition being the origin for all users, and Figure 3b shows the same for a randomly picked initial condition. Although the delays are larger than the theoretical bound $r_{max} < 0.05$, the system can be seen to be stable.




Fig. 4. Flow rates of three users versus time on the basic topology shown.

We next explore extensions to general topologies. Due to computational limitations of the *dde23* solver, we choose a simple network topology with two links as shown in Figure 4. The propagation delay between the two links is 0.2 and users' delays to their corresponding links are chosen randomly with a uniform distribution in the range $[0.1, 0.3]$. Cost parameters are $u = 5$ and $\alpha = 0.5$ and are symmetric for all three users. The results observed in Figure 4 are also in accordance with the results of Theorem IV.1.

VI. CONCLUSION

In this paper we have analyzed the stability properties of an end-to-end congestion control scheme under fixed heterogeneous delays, and general network topologies. The scheme analyzed is based on a congestion control game within the framework of noncooperative game theory and captures a fairly general class of cost functions. The users under this scheme use a standard gradient algorithm to update their flow rates. We present a sufficient condition for global stability of

the unique Nash equilibrium of this game for general network topologies and under a mild symmetricity assumption. The upper-bound on communication delays given in the sufficient condition is inversely proportional to the square root of the number of users multiplied by the cube of a gain constant. We note that this structure is similar to those of local stability results reported in other studies [6]–[8].

Finally, we evaluate stability of the congestion control scheme numerically for various delays, user numbers, and simple topologies for a specific cost structure. The theoretical and numerical analyzes indicate a fundamental tradeoff between the responsiveness of the user update algorithm and the stability properties of the system under communication delays.

REFERENCES

- [1] T. Alpcan and T. Başar, "A game-theoretic framework for congestion control in general topology networks," in *Proc. of the 41st IEEE Conference on Decision and Control*, Las Vegas, NV, December 2002, pp. 1218–1224.
- [2] F. Kelly, A. Maulloo, and D. Tan, "Rate control in communication networks: shadow prices, proportional fairness and stability," *Journal of the Operational Research Society*, vol. 49, pp. 237–252, 1998.
- [3] F. P. Kelly, "Charging and rate control for elastic traffic," *European Transactions on Telecommunications*, vol. 8, pp. 33–37, January 1997.
- [4] R. J. La and V. Anantharam, "Charge-sensitive TCP and rate control in the internet," in *Proc. IEEE Infocom*, 2000, pp. 1166–1175. [Online]. Available: citeseer.nj.nec.com/320096.html
- [5] —, "Utility-based rate control in the internet for elastic traffic," *IEEE/ACM Transactions on Networking*, vol. 10, no. 2, pp. 272–286, April 2002.
- [6] G. Vinnicombe, "On the stability of networks operating TCP-like congestion control," in *Proc 15th IFAC World Congress on Automatic Control*, Barcelona, Spain, July 2002.
- [7] L. Massoulié, "Stability of distributed congestion control with heterogeneous feedback delays," *IEEE Transactions on Automatic Control*, vol. 47, no. 6, pp. 895–902, June 2002.
- [8] R. Johari and D. Tan, "End-to-end congestion control for the internet: delays and stability," *IEEE/ACM Transactions on Networking*, vol. 9, no. 6, pp. 818–832, December 2001.
- [9] S. Kunniyur and R. Srikant, "A time-scale decomposition approach to adaptive explicit congestion notification (ECN) marking," *IEEE Transactions on Automatic Control*, vol. 47(6), pp. 882–894, June 2002.
- [10] S. Deb and R. Srikant, "Global stability of congestion controllers for the internet," *IEEE Transactions on Automatic Control*, vol. 48, no. 6, pp. 1055–1060, June 2003.
- [11] S. Liu, T. Başar, and R. Srikant, "Controlling the Internet: A survey and some new results," in *Proc. of the 42nd IEEE Conference on Decision and Control*, Maui, Hawaii, December 2003.
- [12] J. Wen and M. Arcak, "A unifying passivity framework for network flow control," in *Proc. IEEE Infocom*, San Francisco, CA, April 2003.
- [13] T. Alpcan and T. Başar, "A utility-based congestion control scheme for internet-style networks with delay," in *Proc. IEEE Infocom*, San Francisco, CA, April 2003.
- [14] D. Bertsekas and R. Gallager, *Data Networks*. 2nd ed. Upper Saddle River, NJ: Prentice Hall, 1992.
- [15] H. K. Khalil, *Nonlinear Systems*. 2nd ed. Upper Saddle River, NJ: Prentice Hall, 1996.
- [16] J. K. Hale and S. M. V. Lunel, *Introduction to Functional Differential Equations*, ser. Applied Mathematical Sciences. New York, NY: Springer Verlag, 1993, vol. 99.
- [17] J. A. Yorke, "Asymptotic stability for one dimensional differential-delay equations," *Journal of Differential Equations*, vol. 7, pp. 189–202, 1970.
- [18] L. F. Shampine and S. Thompson, "Solving delay differential equations with dde23," March 2000, <http://www.radford.edu/~thompson/webddes>.